



A5P ADAPTERS

A5P STUDDED ADAPTER • API 6A

KEY BENEFITS

- API 6A studded adapter
- 7-1/16" top × 5,000 psi bottom flange
- Top flange up to 10,000 psi



A5P STUDDED ADAPTER

OVERVIEW

Apache A5P adapters are API 6A studded flange-by-flange adapters transitioning a 7-1/16" top flange (3,000–10,000 psi) to a 5,000 psi bottom flange, with a threaded top tap.

DIMENSIONAL DATA

TOP FLANGE	BOTTOM FLANGE	TOP TAP	WT (LB)
7-1/16" • 3000 psi	2-1/16" • 5000 psi	2"	124.00
7-1/16" • 3000 psi	2-9/16" • 5000 psi	2-1/2"	117.00
7-1/16" • 5000 psi	2-1/16" • 5000 psi	2"	178.00
7-1/16" • 5000 psi	2-9/16" • 5000 psi	2-1/2"	175.00
7-1/16" • 10000 psi	2-1/16" • 5000 psi	2"	318.00
7-1/16" • 10000 psi	2-9/16" • 5000 psi	2-1/2"	316.00

Weights in lb. Studded top flange × bottom flange with threaded top tap.

STANDARDS & OPTIONS

Specification	API 6A	Bottom Flange	2-1/16" – 2-9/16" • 5,000 psi
Type	Studded flange × flange adapter	Top Tap	2" / 2-1/2"
Top Flange	7-1/16" (3,000 / 5,000 / 10,000 psi)		

QUALITY. INTEGRITY. RELIABILITY.

Engineered solutions for demanding environments.

 www.apachemfg.com

GREATER HOUSTON

8809 Bailey Rd
Manvel, TX 77578
(713) 941-1669

ODESSA

2650 West Remington Rd
Odessa, TX 79763
(432) 385-7470