



B2P ADAPTERS

B2P STUDDED ADAPTER • API 6A

KEY BENEFITS

- API 6A studded adapter
- Flange × flange with UPTBG tap
- Up to 5,000 psi



B2P STUDDED ADAPTER

OVERVIEW

Apache B2P adapters are API 6A studded flange-by-flange tubing head adapters with a UPTBG tap, transitioning a 7-1/16" top flange to a smaller bottom flange across 3,000–5,000 psi.

DIMENSIONAL DATA

TOP FLANGE	BOTTOM FLANGE	THREAD	WT (LB)
7-1/16" • 3000 psi	2-9/16" • 5000 psi	2-7/8" UPTBG	170.00
7-1/16" • 3000 psi	3-1/8" • 5000 psi	3-1/2" UPTBG	225.00
7-1/16" • 5000 psi	2-1/16" • 5000 psi	2-3/8" UPTBG	160.00
7-1/16" • 5000 psi	2-9/16" • 5000 psi	2-7/8" UPTBG	230.00
7-1/16" • 5000 psi	3-1/8" • 5000 psi	3-1/2" UPTBG	330.00

Weights in lb. Studded top flange × bottom flange with UPTBG tap.

STANDARDS & OPTIONS

Specification	API 6A	Bottom Flange	2-1/16" – 3-1/8"
Type	Studded flange × flange adapter	Tap / Thread	UPTBG
Top Flange	7-1/16" (3,000 – 5,000 psi)		

QUALITY. INTEGRITY. RELIABILITY.

Engineered solutions for demanding environments.

www.apachemfg.com

GREATER HOUSTON

8809 Bailey Rd
Manvel, TX 77578
(713) 941-1669

ODESSA

2650 West Remington Rd
Odessa, TX 79763
(432) 385-7470