



E-SERIES

API 6A EXPANDING GATE VALVE

KEY BENEFITS

- API 6A · 5,000 psi
- Expanding wedge gate · mechanical seal
- Flanged or threaded LP / EUE · 2-1/16"–7-1/16"



E-SERIES EXPANDING GATE VALVE


OVERVIEW

The Apache E-Series is an API 6A expanding (wedge) gate valve for oil & gas wellheads, production trees, and other critical applications. The wedge gate forms a mechanical seal that does not rely on line pressure, delivering positive 5,000 psi shut-off in 2-1/16" through 7-1/16" bores, with flanged ends or threaded line-pipe / EUE tubing connections.

DIMENSIONAL DATA

END	SIZE	PRESSURE	BORE	B	C	D	E	TURNS	WT (LB)
Flanged	2-1/16"	5,000	2.06	9.62	5.3	19.6	13	13	126
Flanged	2-9/16"	5,000	2.56	10.25	6.1	20.6	13	15-1/2	142
Flanged	3-1/8"	5,000	3.12	11.38	7.6	22.8	16	20	236
Flanged	4-1/16"	5,000	4.06	13.00	9.4	25.9	16	24-1/2	454
2" LP	2-1/16"	5,000	2.06	14.62	5.3	19.6	13	13	176
2-3/8" EUE	2-1/16"	5,000	2.06	14.62	5.3	19.6	13	13	176
2-7/8" EUE	2-9/16"	5,000	2.56	16.62	6.1	20.6	13	15-1/2	224
3" LP	3-1/8"	5,000	3.12	16.62	7.6	22.8	16	20	334
3-1/2" EUE	3-1/8"	5,000	3.12	16.62	7.6	22.8	16	20	334
4" LP	4-1/16"	5,000	4.06	21.62	9.4	25.9	16	24-1/2	614
4-1/2" EUE	4-1/16"	5,000	4.06	21.62	9.4	25.9	16	24-1/2	614

Pressure in psi; dimensions in inches; weights in lb. B = end-to-end length · Turns = handwheel turns to open.
Threaded ends: LP = line pipe, EUE = external-upset tubing. Larger bores to 7-1/16" available – consult factory.



STANDARDS & OPTIONS

Specification	API 6A	End Connections	Flanged or threaded (LP / EUE)
Pressure Rating	5,000 psi	Trim	Material / temperature classes per API 6A
Bore Sizes	2-1/16" – 7-1/16"	Applications	Wellheads, production trees, critical service
Gate	Expanding wedge gate (mechanical seal)		

QUALITY. INTEGRITY. RELIABILITY.

Engineered solutions for demanding environments.

 www.apachemfg.com

GREATER HOUSTON

8809 Bailey Rd
Manvel, TX 77578
(713) 941-1669

ODESSA

2650 West Remington Rd
Odessa, TX 79763
(432) 385-7470